




specification

DS54


LOA	17.17 m	56' 4"
LH	16.71 m	54' 10"
LWL	15.55 m	51' 0"
Beam	5.19 m	17' 0"
Draft		
standard	2.69 m	8' 10"
option	2.34 m	7' 8"
Displacement approx.		
standard	24.70 t	54,454 lbs
option	24.90 t	54,895 lbs
Ballast approx.	6.38 t	14,059 lbs
Engine	150 PS	150 hp
Fresh water approx.	766 l	202 gal
Fuel tank approx.	522 l	138 gal
CE Certificate	A - 12	
Mast length above WL	24.80 m	81' 4"
Main sail approx.	80.80 m ²	870 sq ft
Jib approx.	61.80 m ²	665 sq ft
Genoa approx.	102.60 m ²	1,104 sq ft
Genaker approx.	177.40 m ²	1,910 sq ft
Total sail area approx.	142.60 m ²	1,535 sq ft
Rig		
I	21.41 m	70' 3"
J	6.40 m	21' 0"
P	20.70 m	67' 11"
E	7.10 m	23' 4"
Design	Dixon Yacht Design	
Interior	Design Unlimited	




deck- & interior layouts DS54



Standard




Standard




Option



Option



Option



Option

standard specification DS54

HULL

- 12 hull windows (6 each side)
- GRP hull, isophthalic gelcoat, colour Off White (similar RAL 9003), 1st layer vinyl ester resin and balsa sandwich laminat
- Waterline and cove line, gelcoat colour: Moody Grey (similar RAL 7034)

KEEL

- L-keel, cast iron, draft: 2.69 m
- GRP rudder with sea-water resistant aluminium shaft and selfaligning bearings

LAYOUT & INTERIOR

- A1: Sail locker with extensive storage space
- B1: Master cabin with island double berth, storage space and a head with separate shower stall
- C1: 2 guest cabins with VIP cabin on port incl. long. "Queen size" bed and separate head and guest cabin on stb with double berth (only with D1 layout)
- D1: Saloon with full functional U-galley and dining area on port - chart table on stb
- E1: Aft cabin on port with locker and separate head and utility room on stb
- 3-burner gas stove with oven, waste bin, 12 V fridge approx. 130 l, sink with mixing tab
- Interior furniture in high quality marine plywood, satin varnished

- Sliding door in deck house
- Worktop in galley - Marine Mineral Stone, colour: Grained Black

WOOD (FURNITURE, FLOORBOARD)

- Furniture - Traditional Mahogany - satin varnish
- Floorboard - New Zealand Acacia

UPHOLSTERY

- Comfort mattresses for all berths
- Upholstery - Corsica, colour: cream

DECK & OUTSIDE EQUIPMENT

- GRP deck, gelcoat colour: Off White (similar RAL 9003), 1st layer vinylester resin with balsa sandwich core. Cockpit locker on stb, dinghy garage, anchor locker at bow, stowage for running rigging at helm position.
- Synthetic teak on cockpit bottom, -benches and side deck (colour selection)
- Twin wheel steering system
- Cockpit table, stainless steel with folding teak tops
- Pulpit and pushpit, stainless steel
- Railing, stainless steel tube and wire, incl. integrated boarding ladder on both sides and swimming ladder

- Covered halyards and control lines lead to cockpit helmposition, organizers and jammers, 10 retractable mooring cleats, handrail on coachroof, bow anchor fitting with double roller
- 2 LEWMAR 65 CAST electrical winches with automatic fuse
- Bathing platform, hydraulic fold-out and remote control
- Anchor windlass, electrical, 2000 W, with automatic fuse, wireless remote control with chain counter
- Delta-anchor 40 kg, galvanized with 60 m galvanized chain
- Self tacking jib system
- Mainsheet system
- Panoramic deck saloon windows and glass roof with 2 big hatches, openable and 2 small hatches, openable. Portlight in foredeck with 2 big hatches, openable and 4 small hatches, openable. 6 coach roof portlights, openable and 1 window in cockpit, openable.

RIG & SAILS

- Rig, anodized aluminium with electrical inmast furling system, kicker, standing and running rigging
- Manual jib furler
- Bimini with sliding mechanism (colour selection)

standard specification DS54

- ELVSTRØM Blue Water Dacron sails - full battened, main and jib

NAVIGATION & INSTRUMENTS

- Illuminated compass at each helm
- Navigation lights - LED
- Raymarine i70s multifunction display in cockpit, incl. transducer (speed/depth/temperature)

PROPULSION

- Fuel tank, approx. 522 l
- Engine (Diesel, approx. 146 hp) - shaft drive, propeller 4 blade, folding
- Electronic throttle control at helm position, on stb
- Bowthruster, 24 V, retractable, incl. battery

EQUIPMENT

- 12 V and 230 V electric system with digital switchboards, bus system, 230 V shore power and sockets in cabins and heads
- Battery set, capacity: 1x 90 Ah + 4x 160 Ah AGM
- Country Version: EU / AUS
- Inverter/charger, incl. AC panel (only with XH1001)
- Manual toilet with sea water flush (E1 layout)
- Manual toilet with sea water flush, stb
- Manual toilet with sea water flush, ps
- Shower unit in cockpit, warm-/coldwater
- LPG gas system, stowage for 2 bottles

- Blackwater system (appr. 85 l per head) with deck extraction and seacock
- Freshwater system with electric pump and 40 l hotwater, heated also by main engine
- Fresh water tank, appr. 766 l
- Automatic fire extinguishing system in engine room

SHIPPING & TRANSPORT

- CE - Certificate cat. A - 12
- Owners manual
- EC - Type Examination Certificate